

SMOKING KIT

Kit for smoking foods inside the cooking chamber of combi ovens with capacity 1/1, 2/1 or 2/3 GN. AISI 304 stainless steel drawer with two internal baskets for wood chips and flavourings. Two heating elements for strong or soft, hot or cold smoking. Three smoking levels: standard, soft and strong. Complete with smoker-oven connection pipe, with convenient knob for connection to the oven air inlet pipe, easy to remove and wash. Compatible with COMBISTAR FX, COMBISTAR BX and COMBIFIT (with KFMSXCF accessory).



Functional features

- Three smoking levels: standard, soft and strong.
- Standard smoking for a balanced flavour in long processes such as low-temperature cooking, oil or fish; soft for a very delicate flavour, ideal for fresh cheeses or small quantities; strong for an intensive flavour in a short time, on salts or raw fish.
- Light always on while programs are running.
- Operation with wooden chips from 3 to 12 mm. Chips of beech and / or oak available as accessories.
- The kit allows easy, clean hot or cold smoking.
- Automatic switch-off.
- The kit can be used for several smoking processes in succession with no need for washing itself between processes.

Constructional features

- AISI 304 structure.
- Electric switch-on and integral controls.
- Placed outside the cooking chamber (does not take up valuable cooking chamber space). The smoking kit can be left on top of the oven even when not in use.
- Drawer with two wood chip drawers, filled separately, allowing differentiation of chip flavouring type and quantity.
- Drawer with double skin front to prevent the user from high temperatures, and convenient burn-preventing handle.
- Drawer mechanically locked during smoking to prevent wood chip fire hazards.
- Complete with smoker-oven connection pipe, with convenient knob for connection to the oven air inlet pipe, easy to remove and wash.
- Two safety positions for smoker-oven connection pipe: 1) in operation with drawer locked; 2) off with pipe disconnected from oven.
- Armoured Heating elements in Incoloy 800.
- Easy access to components for all servicing procedures;
- IPX4 water protection rating.

Standard equipment

- Schuko electric socket.
- Power cord supplied.

Technical Data

Working voltage	230V 1N~ / 50 ÷ 60Hz	Electric Power	2,35 kW
Dimensions	27x37,2x16 cm		