

## PASS-THROUGH ELECTRONIC DISHWASHER 72 BASKETS/HOUR

Pass-through dishwasher, double-walled capote; with atmospheric boiler and break tank. Productivity: 72 baskets/h. 8 washing programs that can be personalized (among those, sanitization/medical). Standard supplied drain pump, detergent and rinse-aid dispenser and Bluewater water cleaning device. Included: basket, basket for plates and insert for cutlery.



<i>Air-gap</i>	yes	<i>Basket dimensions</i>	50 x 50 cm
<i>Blue Water</i>	yes	<i>Boiler</i>	Atmospheric
<i>Capacity</i>	GN 1/1 - 53x37 cm	<i>Detergent dispenser</i>	yes
<i>Double skin</i>	yes	<i>Drain pump</i>	yes
<i>Electronic control</i>	yes	<i>Productivity</i>	72 baskets/h
<i>Rinse aid dispenser</i>	yes		

### Functional features

- THE ATMOSPHERIC BOILER ensures constant water temperature and pressure during rinsing. Allows operation even with low mains water pressure. Prevents the 20-30°C reduction in rinsing temperature found with conventional systems.
- WATER CONSUMPTION: 2 liters / cycle
- BLUWATER - The innovative Blue Water system controls water consumption per cycle while guaranteeing greater water purity with excellent washing results.
- 8 WASHING PROGRAMS for great flexibility and versatility of use: 4 Standard programs: Quick, Normal, Intensive, Self-cleaning and 4 Advanced programs: Glasses, Pans and trays, Cutlery, Sanitization according to EN ISO 15883-6 norm (washing and disinfection for non-invasive, non-critical medical devices and for medical equipment).
- ENERGY SAVING: rinsing at the set temperature with an average lower boiler temperature [programmable].
- QUICK READY - waiting times halved during the switching on and heating phase of the dishwasher by using the boiler power.
- Electronic adjustment of the dispensers from the control panel.
- Alarm log for technical service.
- INPUT: hot water between 30 and 50°C.
- Maximum height: 44.5 cm glasses; plates 45.5 cm. Measure GN: 1/1.

### Constructional features

- Dishwasher made of stainless steel, double-walled structure with sound-absorbent insulation.
- Max capote opening 46.5 cm
- AISI 304 stainless steel filters on the entire surface of the tank. Washing and rinsing impellers in AISI 304 stainless steel.
- Well capacity 22 liters and equipped with 2500 W heating element.
- Atmospheric 10 liter boiler 8000 W
- 700W double-flow wash pump [equivalent 950 W]
- Soft touch electronic interface with smart color LCD screen.
- Sound pressure in free field 58.6 dB (A) measured at a distance of 1 m.

### Safety equipment and approvals

- CE approvals in respect of all directives and regulations.
- Break tank (air gap) standard supplied to guarantee of no return of wash water into the water supply.
- Boiler with working and safety thermostat.
- IPX5 protection rating.

### Standard equipment

- n.1 flat basket 50x50 cm
- n.1 plates basket 50x50 cm

# KE130

· n.1 insert for cutlery



## Technical Data

<i>Working voltage</i>	400V 3N~ / 50Hz	<i>Net Weight</i>	100 kg
<i>Gross Weight</i>	110 kg	<i>Electric Power</i>	8,7 kW
<i>Dimensions</i>	72x84x157 cm	<i>Packing</i>	87x76x154 cm

Lavastoviglie Serie KE  
PASS-THROUGH ELECTRONIC DISHWASHER 72 BASKETS/HOUR