

Mod.	015/24L-dy	L24-dy-plus	L25-dy	L305-dy-CV	
SPECIFICATIONS					
DIMENSIONS l x w x h	670X765X1460	670X765X1460	670X765X1450	670X765X1700	mm
WASHING CAPACITY dishes/H	1080-540-360 (1440)	1080-540-360 (1440)	1080-540-360 (1440)	1080-540-360 (1440)	Nr.
baskets/H	60-30-20	60-30-20	60-30-20	60-30-20	Nr.
WASH CYCLE	60"-120"-180"	60"-120"-180"	60"-120"-180"	60"-120"-180"	Sec.
BASKET SIZE	50 x 50	50 x 50	50 x 50	50 x 50	cm
DISHES PER BASKETS	12÷18 (24)	12÷18 (24)	12÷18 (24)	12÷18 (24)	Nr.
WORK HEIGHT	890	890	890	890	mm
PLATES CLEARANCE	415	415	415	415	mm
VOLTAGE	400 V3N~50Hz	400 V3N~50Hz	400 V3N~50Hz	400 V3N~50Hz	V
ELECTRIC PUMP	1100	1100	1100	1100	W
RINSING ELECTRIC PUMP	option	option	option	385	
WASH TANK ELEMENTS	3000	6000	6000	6000	W
RINSE TANK ELEMENTS	9000	9000	9000	9000	W
TOTAL RATING	10100	10100	10100	10100	W
MAX CURRENT INTENSITY	16	16	16	16	A
TANK CAPACITY	34	34	34	34	Lt
BOILER CAPACITY	8	8	8	8	Lt
RINSE AID DISPENSER	YES	YES	YES	YES	
WASH AID DISPENSER	OPTION	YES	OPTION	OPTION	
SCALE REMOVER PUMP	OPTION	YES	OPTION	OPTION	
DRAIN PUMP	OPTION	30 W	OPTION	OPTION	W
WATER CONNECTION	45 ÷ 55	45 ÷ 55	45 ÷ 55	10 ÷ 12	°C
PUMP DELIVERY	480	480	480	480	l./min
WATER CONSUMPTION PER CYCLE	2.80	2.80	2.80	2.80	l
WATER CONSUMPTION PER HOUR	56-84-168	56-84-168	56-84-168	58-89-117	l
WATER PRESSURE	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	Bar
WATER HARDNESS	5 ÷ 10	5 ÷ 10	5 ÷ 10	5 ÷ 10	°F
RINSING WATER TEMPERATURE	80 ÷ 90	80 ÷ 90	80 ÷ 90	80 ÷ 90	°C
WATER INLET	3/4"	3/4"	3/4"	3/4"	"G
WATER OUTLET	32 mm ÷ 1"1/4	32 mm ÷ 1"1/4	32 mm ÷ 1"1/4	32 mm ÷ 1"1/4	"G
NET WEIGHT	133	133	145	178	kg
GROSS WEIGHT	151	151	164	200	kg
PACKING DIMENSIONS	800x930x1610	800x930x1610	800x930x1610	830x930xh1870	mm
NOISE	63,5	63,5	59,5	<67	dB(A)
STEAM CONDENSER FAN POWER				63	W
STEAM CONDENSER FAN CAPACITY				600	mc/H
HOOD WITH DOUBLE INSULATING WALL	OPTION	OPTION	YES	YES	