



## B04D.26

| CAPACITY, DIMENSIONS, WEIGHT        |   | ///                      |
|-------------------------------------|---|--------------------------|
| Capacity trays                      |   | 4 TRAYS 600x400 - GN 1/1 |
| Distance between trays (mm)         |   | 80                       |
| Type of rack holder                 |   | GRID                     |
| Unit size with handle WxDxH (mm)    |   | 800 x 795 x 577          |
| Unit size without handle WxDxH (mm) |   | 800 x 733 x 577          |
| Chamber size WxDxH (mm)             |   | 694 x 455 x 345          |
| Packaging                           |   | PALLET + CARTON BOX      |
| Packaging size WxDxH (mm)           |   | 850 x 850 x 740          |
| Unit weight (kg)                    |   | 55                       |
| Unit weight with packaging (kg)     |   | 67                       |
| ELECTRICAL DATA                     |   | ///                      |
| Number of engines                   |   | 2                        |
| Frequency (Hz)                      |   | 50                       |
| Power (kW)                          |   | 7,4                      |
| Voltage                             | A | 400V 3N~                 |
|                                     | B | 400V 2N~                 |
|                                     | C | 230V ~                   |
|                                     | D | 230V 3~                  |
| Current (A)                         | A | 12,2                     |
|                                     | B | 22,2                     |
|                                     | C | 32,2                     |
|                                     | D | 21,1                     |

|                                      |   |                    |
|--------------------------------------|---|--------------------|
| Power cord/power plug                |   | A                  |
|                                      |   | B                  |
|                                      |   | C                  |
|                                      |   | D                  |
| <b>WATER CONNECTION REQUIREMENTS</b> |   | ///                |
| Water inlet                          |   | YES                |
| Water drain                          |   | -                  |
| Minimum water quality standards      |   | 5° f               |
| <b>FUNCTIONAL CHARACTERISTICS</b>    |   | ///                |
| Supply                               |   | ELECTRIC           |
| Certification                        |   | CB                 |
| Control panel                        |   | DIGITAL            |
| Multilingual screen                  |   | -                  |
| Cooking type                         |   | CONVECTION         |
| Bidirectional motors                 |   | YES                |
| Two speed regulation                 |   | -                  |
| Max cooking temperature (°C)         |   | 260                |
| Cooking chamber material             |   | AISI 430           |
| Opening door                         |   | FROM TOP TO BOTTOM |
| Easy clean internal glass            |   | -                  |
| <b>STANDARD EQUIPMENT</b>            |   | ///                |
| Self clean system                    |   | -                  |
| Core probe                           |   | -                  |
| <b>VARIANTS AVAIABLES</b>            |   | ///                |
| Certification                        |   | -                  |
| Unit size with handle WxDxH (mm)     |   | 800 x 781 x 577    |
| Unit size without handle WxDxH (mm)  |   | 800 x 733 x 577    |
| Frequency (Hz)                       |   | 60                 |
| Power (kW)                           |   | -                  |
| Voltage                              | A | -                  |
|                                      | B | -                  |
|                                      | C | -                  |
|                                      | D | -                  |
| Current (A)                          | A | -                  |
|                                      | B | -                  |
|                                      | C | -                  |
|                                      | D | -                  |
| Power cord / power plug              |   | A -                |

|                                                                   |   |                          |
|-------------------------------------------------------------------|---|--------------------------|
|                                                                   | B | -                        |
|                                                                   | C | -                        |
|                                                                   | D | -                        |
| Packaging                                                         |   | -                        |
| Packaging size WxDxH (mm)                                         |   | -                        |
| <b>ACCESSORIES</b>                                                |   | ///                      |
| Self clean system                                                 |   | -                        |
| Stainless steel tray rack holder                                  |   | -                        |
| Stainless steel grid rack holder                                  |   | "5 TRAYS GN 1/1<br>67mm" |
| Oven stand                                                        |   | T8                       |
|                                                                   |   | T8S                      |
|                                                                   |   | T8SL                     |
| Wheels kit for stand                                              |   | H8                       |
| Condensation hood                                                 |   | -                        |
| Water condensation hood                                           |   |                          |
| Proofer                                                           |   | CA8008M0                 |
|                                                                   |   | CA8008MH                 |
|                                                                   |   | CA8088DH                 |
| Overlapping kit for 2 ovens                                       |   | CA8016M0                 |
| Blast chiller                                                     |   | SK3                      |
|                                                                   |   | ASP05                    |
|                                                                   |   | -                        |
| Overlapping kit for blast chillere + 1 ovens                      |   | -                        |
| Smoker                                                            |   | -                        |
| Core probe                                                        |   | -                        |
| Core probe for vacuum                                             |   | WS10                     |
| Water softner cover                                               |   | WS11                     |
| Water softner 6800L                                               |   | WS12                     |
| Water softner 12000L                                              |   | WPA                      |
| Water pressure adaptor                                            |   | -                        |
| Manual shower kit                                                 |   | -                        |
| "Detergent 750ML<br>(for Self clean system or Manual shower kit)" |   | -                        |
| "Detergent 6KG<br>(only with self clean system)"                  |   | -                        |
| "Detergent 10KG<br>(only with self clean system)"                 |   | -                        |

## FEATURES

◆ Standard | ◇ Optional | - Not available

### MANUAL COOKING

|                                    |              |   |
|------------------------------------|--------------|---|
| Convection cooking                 | 30°C - 285°C | ◆ |
| Mixed steam and convection cooking | 90°C - 230°C | ◆ |
| Grill                              |              | - |

### AUTOMATIC COOKING

|                                            |     |   |
|--------------------------------------------|-----|---|
| Program: possibility to memorize program   | 99  | ◆ |
| V-EVOLUTION CONTROL WITH 6 SPEED PRO-GRAMS |     | - |
| Cooking cycles for each program            | n°4 | ◆ |
| Automatic pre-heating setting              |     | ◆ |

### AIR DISTRIBUTION IN THE COOKING CHAMBER

|                               |  |   |
|-------------------------------|--|---|
| V-BI.DIRETIONAL REVERSING FAN |  | ◆ |
| V-POWERFULL ENGINE            |  | ◆ |
| Number of speed regulation    |  | - |

### OVERLAP SYSTEM

|                                             |  |   |
|---------------------------------------------|--|---|
| V- OVERLAP CONNECTION with ovens            |  | ◇ |
| V- OVERLAP CONNECTION with Venix's Proofing |  | ◇ |
| V- OVERLAP CONNECTION with Venix's Stand    |  | ◇ |

### OTHER FUNCTIONS

|                                     |  |   |
|-------------------------------------|--|---|
| Infinity time                       |  | ◆ |
| Temperature parameter unit F° or C° |  | ◆ |

|            |         |   |
|------------|---------|---|
| V - LIGHTS | Halogen | ◆ |
| USB        |         | - |

### TECHNICAL DETAILS

|                                                     |         |   |
|-----------------------------------------------------|---------|---|
| Internal glass easy clean system                    |         | ◆ |
| Thermal insulation structure (energetic efficiency) |         | ◆ |
| Water injection regulation                          | Digital | ◆ |